

Model		DS-7604NI-SE
Video/Audio input	IP video input	4-ch, 4CIF
	Voice talk input	1-ch, RCA (2.0 Vp-p, 1kΩ)
Video/Audio output	Decoding resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF /2CIF/CIF/QCIF
	HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz
	CVBS	1-ch, BNC (1.0 Vp-p, 75 Ω) Resolution: 704 × 576 (PAL)
	Audio output	1-ch, RCA (Linear, 1kΩ)
	Playback resolution	5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF
	Synchronous playback	4-ch
Hard disk	SATA	1 SATA interface for 1 HDD
	Capacity	Up to 4TB for each disk
External interface	Network interface	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface
		4 independent 10 /100 Mbps Ethernet interfaces (for built-in switch)
	Serial interface	1 RS-485 half-duplex interface
	USB interface	2 × USB 2.0
	Alarm in/out	4/1 (optional)
Others	Power supply	12V DC
	Consumption	≤ 10 W (without hard disk)
	Working temperature	-10 °C ~ +55 °C
	Working humidity	10 % ~ 90 %
	Chassis	Stand-alone 1U chassis
	Dimensions (W × D × H)	315 × 230 × 45mm
	Weight	≤ 2 Kg ( without hard disk)

Authorized Distributor in Hong Kong



Hotline: (852) 31820888

Fax: (852) 31820808

 E-mail: [cs@wecl.com.hk](mailto:cs@wecl.com.hk)

 Website: [www.WECLonline.com](http://www.WECLonline.com)

Office Address: 1/F, Cheung Lok Building, 199 Cheung Sha Wan Road, Sham Shui Po, Kln, HK